



Product certificate

ADRIFÖL Classic SAE 20W-50 API SC

0002-000021

Description

ADRIFÖL Classic SAE20W-50 API SC is a year round mildly alloyed engine oil whose composition has been specifically tailored to the needs of old and vintage vehicles with an oil filter. Suitable for petrol and diesel engines which have been developed for the multi-grade oils of their time.

ADRIFÖL Classic SAE20W-50 API SC prolongs the life of the engine due to increased concentration of the zinc content. This prevents deposits, wear and leaks. The special viscosity grade ensures stable oil pressure and optimal compression, even at high temperatures.

Instructions for use

ADRIFÖL Classic SAE20W-50 API SC especially suitable for classic cars built after 1950, with oil filter elements, in which a mild alloyed lubricant is required.

ADRIFÖL Classic SAE20W-50 API SC is also further suitable for older engines as well as older circulation lubrication and hydrostatic motors.

Quality classification

Specification

- API SC

ADRIFÖL Classic SAE 20W-50 API SC is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- excellent material compatibility
- prevents calcification and coking of cylinders, pistons and valves
- selected base oils offer high protection against oxidation
- Secure lubricant film at high operating temperatures
- Neutrality towards sealants
- high zinc content to protect against wear
- Excellent protection against wear, corrosion and foaming.
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	18,75	MM ² /S	DIN ISO 51562-2
viscosity index	123		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	881,5	KG/M ³	DIN EN ISO 12185
Pour Point	-27	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.