



Product certificate

ADRIFÖL Classic SAE 50 API SA

0002-000017

Description

ADRIFÖL Classic SAE 50 API SA is a year round unalloyed engine oil whose composition has been specifically tailored to the needs of vintage vehicles without an oil filter. Suitable for petrol and diesel engines which have been developed for the mono-grade oils of their time.

Due to its carefully selected base oils, ADRIFÖL Classic SAE 50 API SA is particularly resistant to oxidation, non-foaming and ensures fewer deposits and less wear because of its low ash content.

Instructions for use

ADRIFÖL Classic SAE 50 API SA is particularly recommended for pre-war engines which don't have oil filters and where sludge can settle in the oil sump.

ADRIFÖL Classic SAE 50 API SA is also suitable for cars with vintage or old gearboxes.

Quality classification

Specification

- API SA

ADRIFÖL Classic SAE 50 API SA is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- excellent material compatibility
- prevents calcification and coking of cylinders, pistons and valves
- selected base oils offer high protection against oxidation
- Secure lubricant film at high operating temperatures
- Neutrality towards sealants
- Excellent protection against wear, corrosion and foaming.
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	17,92	MM ² /S	DIN ISO 51562-2
viscosity index	94		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	891,5	KG/M ³	DIN EN ISO 12185
Pour Point	-9	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:52:02