



Product certificate

ADRIFÖL Semi Synth. 10W-40

0002-000025

Description

ADRIFÖL Semi Synth. 10W-40 is a semi-synthetic high-performance, smooth-running engine oil for carburettor and diesel car engines with or without turbocharging and direct injection. Extended oil change intervals as per manufacturer's instructions.

ADRIFÖL Semi Synth. 10W-40 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. With ADRIFÖL Semi Synth. 10W-40 a reliable and heavy-duty engine oil has been developed.

Instructions for use

ADRIFÖL Semi Synth. 10W-40 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

ADRIFÖL Semi Synth. 10W-40 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- ACEA A3/B4
- API SM/CF

Approval:

- MB-Freigabe 229.1

ADRIFÖL Semi Synth. 10W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- BMW Special Oil
- VW 501 01/505 00
- Fiat 9.55535-G2/D2
- PSA B71 2294

Properties

- Excellent cold starting properties, even at low temperatures below -25°
- A very stable and excellent viscosity behaviour and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Extensive protection against wear, corrosion and foam-ing.
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	93,2	MM ² /S	DIN ISO 51562-2
Kinematic Viscosity at 100°C	13,9	MM ² /S	DIN ISO 51562-2
viscosity index	151		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	865	KG/M ³	DIN EN ISO 12185
pour point	-36	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.