# Product certificate

## ADRIFÖL ATF M-9-FE (Red) 0002-000179

## Description

ADRIFÖL ATF M-9-FE is designed on a basis of hydrocrack oils and PAO with special additives and inhibition, which guarantee the flawless function of the automatic gearbox.
ADRIFÖL ATF M-9-FE is an ATF of the latest generation for all automatic gearboxes. A high wear protection is guaranteed in all operating conditions.

## Instructions for use

ADRIFÖL ATF M-9-FE Colorless was developed for use in Mercedes automatic gearboxes 7G-TRONIC with ECO stop-start function (NAG2FE+).

## Quality classification

**Specification**

**ADRIFÖL ATF M-9-FE (Red) is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

- MB 236.15
- MB A001 989 78 03, MB A001 989 77 03
- ATF 7134 FE; ATF 134 FE; ATF 134 ME

## Properties

- Very high temperature and ageing stability, i.e. high protection against deposits
- High and stable viscosity index
- Good lubrication properties, even at low temperatures in winter
- Excellent oxidation stability
- Coordinated friction properties
- High thermal and oxidative stability
- Excellent cooling capacity
-

## Technical specifications

| Properties | Data | Unit | Testing under |
|---|---|---|---|
| kinematic viscosity at 100°C | 4,400 | MM²/S | DIN ISO 51562-2 |
| viscosity index | 157 | | DIN ISO 2909 |
| appearance | RED | | visually |
| density at 15°C | 832,0 | KG/M³ | DIN EN ISO 12185 |
| Pour Point | -63 | CELSIUS | ASTM D 7346 |

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:55:32