



Product certificate

ADRIFÖL CLP 220 VCI

0002-000276

Description

ADRIFÖL CLP 220 VCI is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of ingredients, it achieves a stable, high-pressure capacity under impact loads.

Due to incorporated volatile corrosion inhibitors ADRIFÖL CLP 220 VCI offers excellent anti-corrosion properties even above the oil surface.

Instructions for use

ADRIFÖL CLP 220 VCI can be used in largely all industrial areas under stress and impact loads, where a CLP oil according to DIN 51517 Part 3 is recommended.

ADRIFÖL CLP 220 VCI is recommended for gears that need special corrosion protection in maritime areas due to standstill periods.

Quality classification

Specification

- DIN 51517 Part 3

ADRIFÖL CLP 220 VCI is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- AGMA 9005-D94
- Cincinnati Milacron
- US Steel 224
- Clean Panel Coker
- S-200 Oxidation Tubes

Properties

- A stable, high-pressure capacity under impact loads
- An excellent cold behaviour
- A low pour point
- An excellent wear protection
- Inhibits rust and corrosion
- Prevents foam formation
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	225,500	MM ² /S	DIN ISO 51562-2
viscosity index	94		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	896,0	KG/M ³	DIN EN ISO 12185
Pour Point	-21	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.