



Product certificate

ADRIFÖL CVT Fluid

0002-000170

Description

ADRIFÖL CVT Fluid is a latest generation automatic gearbox lubricant for CVT automatic gearboxes.

ADRIFÖL CVT Fluid guarantees optimum power transmission.

ADRIFÖL CVT Fluid is designed on a basis of synthetic oils with special additives and inhibition, which guarantee the flawless function of the automatic gearbox.

Instructions for use

ADRIFÖL CVT Fluid was developed for use in CVT automatic gearboxes (belt CVTs and chain CVT).

ADRIFÖL CVT Fluid ensures a stable viscosity, even under the highest mechanical stresses in the transmission elements (push belt).

Quality classification

Specification

ADRIFÖL CVT Fluid is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Audi TL 52 180 (G 052 180), TL 52 516 (G052 516)
- BMW/Mini (EZL799)
- Daihatsu TC/Amix CVTF-DC/-DFE
- Dodge/Jeep NS-2/CVTF+4
- Ford (CVT23/30) Mercon C
- GM / SATURN DEX-CVT
- Honda HMMF/HFC-2
- Renault ELFMATIC
- KIA/Hyundai CVTF
- Mercedes Benz MB 236.20
- Mitsubishi Dia/Queen NS-2;CVT-Fluid J1/J4
- Nissan NS-2/-3
- Subaru NS-2 / Linatronic CVTF
- Suzuki TC/NS-2/CVT Green 1/2
- Toyota TC

Properties

- Very good lubrication properties, even at low temperatures in winter.
- Very high and stable viscosity index
- Very low pour point
- Very good oxidation stability
- Most extensive protection against wear, corrosion and foaming
- Well coordinated friction properties
- Neutral behaviour towards sealing agents
- Neutral behaviour towards non-ferrous metals due to inhibition
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	7,373	MM ² /S	DIN ISO 51562-2
viscosity index	187		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	840,6	KG/M ³	DIN EN ISO 12185
Pour Point	-51	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

