Product certificate

ADRIFÖL Circulating Oil CL 150 0002-000272

Description

ADRIFÖL CL Circulating Oil 150 is produced on a basis of high-quality mineral oils and proven additives. Thanks to its special combination of active ingredients, it is suitable for use as a simple machine lubricant where no EP-additive oils are required.

Instructions for use

ADRIFÖL CL Circulating Oil 150 has very good properties as a lubricant.
Therefore ADRIFÖL CL Circulating Oil 150 can preferably be used for industrial gears and circulation systems of low and medium loads, where lubricants are required in accordance with DIN 51517-2.

Quality classification

Specification

- DIN 51517-2 (CL)

ADRIFÖL Circulating Oil CL 150 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- A mild additive and is therefore particularly suitable for old machines
- A good wear protection
- Inhibits rust and corrosion and protects against ferrous metal corrosion.
- Prevents foam formation
- Good water seperation characteristics
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	148,600	MM^2/S	DIN ISO 51562-2
viscosity index	90		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	892,0	KG/M^3	DIN EN ISO 12185
Pour Point	-27	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:58:04