



Product certificate

ADRIFÖL Compressor Oil VDL 150

0002-000281

Description

ADRIFÖL Compressor Oil VDL 150 is produced on the basis of high-quality, age-resistant base oils, and thus fulfils the high requirements of DIN 51506.

ADRIFÖL Compressor Oil VDL 150 has a good adhesive power, is water repellent and reduces wear, as it exhibits low residue formation.

Instructions for use

ADRIFÖL Compressor Oil VDL 150 can be used up to 220°C in stationary and mobile compressors with compression temperatures.

ADRIFÖL Compressor Oil VDL 150 is also used for the circular lubrication of driving mechanisms and diesel engines if the manufacturer does not prescribe any HD engine oils.

Quality classification

Specification

- DIN 51506 (VBL, VCL, VDL)
- ISO/DP 6521 (DAA, DAB, DAH, DAG)

ADRIFÖL Compressor Oil VDL 150 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- ALUP
- ATLAS COPCO
- AUDI
- CompAir
- FIAC
- FINI
- KAESER

Properties

- Excellent resistance to ageing
- Neutrality towards sealants
- Very good viscosity and temperature behaviour
- reliable wear protection
- low coking tendency
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	15,800	MM ² /S	DIN ISO 51562-2
viscosity index	102		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	886,0	KG/M ³	DIN EN ISO 12185
Pour Point	-15	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

11.01.2019 01:00:05