



## Product certificate

**ADRIFÖL Dexron D II (rot)**

**0002-000157**

### Description

ADRIFÖL Dexron D II is a very high-quality gear fluid for automatic gearboxes of all vehicles and machinery. ADRIFÖL Dexron D II is made with a base of highly refined mineral oils with suitable additives. It was developed especially for the indicated specifications and purposes.

ADRIFÖL Dexron D II provides maximum lubrication and wear protection thanks to its special additives.

### Instructions for use

ADRIFÖL Dexron D II was developed for use in automatic gearboxes, hydraulic steering systems, converters and power transmissions, and can be used as a universal ATF (automatic transmission fluid) for all vehicles and machinery.

ADRIFÖL Dexron D II is recommended if an ATF type Dexron DII must be used in accordance with the manufacturer's specifications. The operating instructions of the automobile and engine manufacturer must be observed.

### Quality classification

#### Specification

- GM Dexron D II
- Renk Doromat

**ADRIFÖL Dexron D II (rot) is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

- Ford SQM-9010B, M2C-138 CJ, 166H, 185A
- Ford Mercon
- MB 236.6, 236.7
- Caterpillar TO-2
- VOITH 55.6335.xx
- MAN 339 Typ Z-1
- ZF TE-ML 03D, 04D, 11A, 14A, 17C, 05L

### Properties

- Reliable protection against wear, silting, bonding and corrosion
- Stable and excellent viscosity-temperature behaviour
- Problem-free, both at very low and very high temperatures
- Foam-free, even under the heaviest of loads
- Extremely high thermal load bearing capacity
- Miscibility and compatibility with all brands of ATFs
- Neutral towards sealing agents.
- 

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	7,200	MM²/S	DIN ISO 51562-2
viscosity index	167		DIN ISO 2909
appearance	RED		visually
density at 15°C	852,0	KG/M³	DIN EN ISO 12185
Pour Point	-48	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.