



Product certificate

ADRIFÖL Diesel Super 10W-30

0002-000102

Description

Diesel Super 10W-30 is a high-quality modern multigrade engine oil for car engines of all makes, with or without turbocharging. Diesel Super 10W-30 allows for extended oil change intervals in accordance with manufacturer's instructions.

Diesel Super 10W-30 is suitable for year-round use in all engines. minimization of friction, wear and fuel consumption, good cold starting properties.

Instructions for use

Diesel Super 10W-30 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Diesel Super 10W-30 is suitable as a year-round oil for petrol and diesel car engines.

Quality classification

Specification

- ACEA E2
- API CF-4

Approval:

- Allison C-4
- Caterpillar TO-2
- MAN 271
- MB 228.1
- MTU Typ 2
- Volvo VDS
- VW 505 00

ADRIFÖL Diesel Super 10W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- Good cold starting properties
- A very stable and excellent viscosity behaviour and shear stability
- High oxidation stability
- Good detergent and dispersing properties
- High safety margin even in boundary lubrication
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	11,500	MM²/S	DIN ISO 51562-2
viscosity index	156		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	862,0	KG/M³	DIN EN ISO 12185
Pour Point	-42	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.