



Product certificate

ADRIFÖL Euro 6 Diesel 10W-30

0002-000101

Description

ADRIFÖL Euro 6 Diesel 10W-30 is a universal engine oil on a basis of selected base oils combined with the latest additives for all diesel engines with or without turbo-charging in lorries, buses and machinery.

With ADRIFÖL Euro 6 Diesel 10W-30, a reliable engine oil has been developed.

Instructions for use

ADRIFÖL Euro 6 Diesel 10W-30 is an engine oil suitable for year-round use. It was designed for the new exhaust emission guidelines including for vehicles with exhaust gas recirculation systems.

ADRIFÖL Euro 6 Diesel 10W-40 is universally applicable in all diesel engines with and without turbocharging.

Quality classification

Specification

- ACEA E6/E7
- API CI-4

Approval:

- Renault VI RLD-2
- Volvo VDS-3
- MACK EO-N

ADRIFÖL Euro 6 Diesel 10W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- JASO DH-2
- MAN M3271-1 / M3477
- MB 228.51 / MB 226.9
- MTU Type 3.1
- Cummins CES 20076/77
- DAF
- Deutz DQC-III-10 LA, DCQ TTCD
- Renault Trucks RLD-2 / RXD / RGD1

Properties

- Excellent oxidation stability
- Very good high-temperature stability
- Excellent detergent and dispersant properties
- Efficiency due to low fuel consumption
- Excellent cold starting performance; a fast engine lubrication even at low temperatures
- Very good viscosity and temperature behaviour
- Neutrality towards sealants
- High wear protection

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	12,200	MM ² /S	DIN ISO 51562-2
viscosity index	148		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	859,0	KG/M ³	DIN EN ISO 12185
Pour Point	-39	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.