



Product certificate

ADRIFÖL Excellence FDL 5W-30

0002-000068

Description

ADRIFÖL Excellence FDL 5W-30 is a synthetic Mid SAPS smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. ADRIFÖL Excellence FDL 5W-30 is characterized by its excellent cold starting properties and its minimization of fuel consumption, friction and wear. Thanks to its formulation with special base oils, ADRIFÖL Excellence FDL 5W-30 achieves a high viscosity index. The excellent cold starting performance ensures optimum lubrication reliability in the cold-running phase.

Thanks to significant fuel savings and the reduction of emissions, ADRIFÖL Excellence FDL 5W-30 contributes to the protection of the environment. Extended oil change intervals as per manufacturer's instruction.

Instructions for use

ADRIFÖL Excellence FDL 5W-30 is a universal, synthetic smooth-running engine oil, which has been developed specifically for use in engines with the OEM requirements indicated.

Quality classification

Specification

- ACEA C2
- JASO DL-1
- API SM
- ILSAC GF-4

ADRIFÖL Excellence FDL 5W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Fiat 9.55535-S1
- Iveco 18-1811 Classe SC1
- PSA B71 2290

Properties

- Excellent cold starting properties, even at low temperatures below -30°
- The function of the hydraulic valve lifter is guaranteed at all temperatures
- Fuel savings in all operating conditions
- A secure lubricant film at high operating temperatures
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources
- MID SAPS = reduced sulphated ash, phosphorous and sulphur
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming.

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	55,7	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	10,2	MM ² /S	DIN ISO 51562-2
viscosity index	174		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	848	KG/M ³	DIN EN ISO 12185
Pour Point	-42	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.