



Product certificate

ADRIFÖL FS 0W-40

0002-000071

Description

ADRIFÖL FS 0W-40 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. ADRIFÖL FS 0W-40 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear. Extended oil change intervals as per manufacturer's instructions. With ADRIFÖL FS 0W-40 a reliable and heavy-duty engine oil has been developed to guarantee the low viscosity of SAE 0W-class as well as a low evaporation loss.

Instructions for use

ADRIFÖL FS 0W-40 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines. ADRIFÖL FS 0W-40 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturers must be observed.

Quality classification

Specification

- ACEA A3/B4
- API SN/CF

ADRIFÖL FS 0W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- BMW Longlife-01
- Fiat 9.55535-M2/Z2
- MB 229.5/229.3/226.5
- Ford WSS-M2C937-A
- Porsche A40
- PSA B71 2296
- VW 502 00/505 00
- Renault RN0700/0710

Properties

- Excellent cold starting properties, even at temperatures below -30°
- A very stable and excellent viscosity behavior, shear stability
- Fuel savings in all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Excellent protection against wear, corrosion and foaming.
- Suitability for catalytic converters
- Extended oil change intervals protect natural resources

Technical specifications

| Properties | Data | Unit | Testing under |
|------------------------------|-------------|--------------------|------------------|
| kinematic viscosity at 40°C | 72,9 | MM ² /S | DIN ISO 51562-2 |
| kinematic viscosity at 100°C | 13,5 | MM ² /S | DIN ISO 51562-2 |
| viscosity index | 190 | | DIN ISO 2909 |
| appearance | YELLOWBROWN | | visually |
| density at 15°C | 848 | KG/M ³ | DIN EN ISO 12185 |
| Pour Point | -42 | °C | ASTM D 7346 |

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

17.07.2018 02:01:01