



## Product certificate

**ADRIFÖL FS 10W-40**

**0002-000054**

### Description

ADRIFÖL FS 10W-40 is a synthetic high-performance, smooth-running engine oil for carburettor and diesel car engines with or without turbocharging and direct injection. Extended oil change intervals as per manufacturer's instructions.

ADRIFÖL FS 10W-40 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear.

With ADRIFÖL FS 10W-40, a reliable and heavy-duty engine oil has been developed.

### Instructions for use

ADRIFÖL FS 10W-40 is an engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

ADRIFÖL FS 10W-40 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

### Quality classification

#### Specification

- API SM/CF
- ACEA A3/B4

**ADRIFÖL FS 10W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

- BMW Special Oil
- VW 501 01 / 505 00
- MB 229.1
- VW 502 00 / 500 00

### Properties

- Excellent cold starting properties, even at low temperatures below -25°
- A very stable and excellent viscosity behavior and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Extensive protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	13,480	MM <sup>2</sup> /S	DIN ISO 51562-2
viscosity index	158		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	860,5	KG/M <sup>3</sup>	DIN EN ISO 12185
Pour Point	-39	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.