



Product certificate

ADRIFÖL FS 5W-20

0002-000046

Description

FS 5W-20 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection.

FS 5W-20 is characterized by its excellent cold starting properties, minimization of fuel consumption,

friction and wear. Thanks to significant fuel savings and the reduction of emissions, ADRIFÖL FS 5W-20 contributes to the protection of the environment.

Instructions for use

FS 5W-20 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

Quality classification

Specification

- API SN (RC)
- ILSAC GF-5

ADRIFÖL FS 5W-20 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Fiat 9.55535-CR1
- Ford WSS-M2C930-A
- Ford WSS-M2C945-A
- Chrysler MS-6395
- GM 6094M

Properties

- Excellent cold starting properties, even at low temperatures
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Extensive protection against wear, corrosion and foaming.
- Extended oil change intervals protect natural resources
- No oil-dependent deposits in combustion chambers, in the piston ring area or on valves

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	47,8	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	8,2	MM ² /S	DIN ISO 51562-2
viscosity index	147		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	856	KG/M ³	DIN EN ISO 12185
Pour Point	-42	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.