



Product certificate

ADRIFÖL FS 5W-40

0002-000030

Description

ADRIFÖL FS 5W-40 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. ADRIFÖL FS 5W-40 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear.

With ADRIFÖL FS 5W-40, a reliable and heavy-duty engine oil has been developed to guarantee the low viscosity of SAE 5W-class as well as a low evaporation loss. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

ADRIFÖL FS 5W-40 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

ADRIFÖL FS 5W-40 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SN/CF
- ACEA A3/B4

Approval:

- MB-Freigabe 229.3

ADRIFÖL FS 5W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- BMW Longlife-98
- Porsche A40 ab Modeljahr 1973 (außer Cayenne V6)
- Renault RN0700/0710
- VW 502 00/505 00
- Fiat 9.55535-H2/M2/N2
- Opel GM-LL-B-025
- PSA B71 2296

Properties

- Excellent cold starting properties, even at low temperatures below -30°C.
- A very stable and excellent viscosity behavior and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	86,6	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	14,1	MM ² /S	DIN ISO 51562-2
viscosity index	169		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	856	KG/M ³	DIN EN ISO 12185
Pour Point	-42	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

