



Product certificate

ADRIFÖL FS Dexron II E (rot)

0002-000184

Description

ADRIFÖL FS Dexron II E is a very high-quality, synthetic gear fluid for automatic gearboxes of vehicles with the specifications GM Dexron II E, Ford Mercon and Allison C4.

Instructions for use

ADRIFÖL FS Dexron II E was developed for use in built-in automatic gearboxes as well as torque converters and power shift gears with prescribed specifications.

ADRIFÖL FS Dexron II E is recommended if an ATF type Dexron II E must be used in accordance with the manufacturer's specifications.

Quality classification

Specification

ADRIFÖL FS Dexron II E (rot) is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Allison C4-32652009 (ATF II E)
- Ford Mercon
- GM Dexron II E
- Voith 55.6336.3x Extended Drain (G1363)
- Cat. TO-2
- MAN 339 Typ Z-2, MAN 339 Typ V-2
- MB 236.8, MB 236.5
- TE-ML 04D, 09X, 14B, 16L

Properties

- Very stable viscosity-temperature behaviour
- Reliable protection against wear, silting and corrosion
- Problem-free, both at very low and very high temperatures
- High thermal load capacity
- Foam-free
- Neutral towards sealing agents
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	7,000	MM ² /S	DIN ISO 51562-2
viscosity index	189		DIN ISO 2909
appearance	RED		visually
density at 15°C	836,0	KG/M ³	DIN EN ISO 12185
Pour Point	-54	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:55:38