



Product certificate

ADRIFÖL FS Dura Fusion 5W-30

0002-000056

Description

ADRIFÖL FS Dura Fusion 5W-30 is a synthetic Low SAPS smooth-running engine oil for petrol and diesel car engines. It is particularly well suited to modern diesel engine with particle filters.

ADRIFÖL FS Dura Fusion 5W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear.

ADRIFÖL FS Dura Fusion 5W-30 contributes to the protection of the environment. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

ADRIFÖL FS Dura Fusion 5W-30 is a universal, synthetic smooth-running engine oil, which has been developed especially for pump-nozzle diesel engines.

ADRIFÖL FS Dura Fusion 5W-30 is suitable for petrol and diesel engines in cars and transporters with and without turbochargers.

Quality classification

Specification

- ACEA C4

Approval:

- MB-Freigabe 226.51
- Renault RN0720

ADRIFÖL FS Dura Fusion 5W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- MB 229.51/229.31
- Fiat 9.55535-S4

Properties

- Excellent cold starting properties, even at low temperatures below -30°
- The function of the hydraulic valve lifter is guaranteed at all temperatures
- Fuel savings under all operating conditions
- A secure lubricant film at high operating temperatures
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming.
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources
- Low SAPS = reduced sulphated ash, phosphorous and sulphur

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	70,8	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	11,9	MM ² /S	DIN ISO 51562-2
viscosity index	165		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	847	KG/M ³	DIN EN ISO 12185
Pour Point	-39	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.