



Product certificate

ADRIFÖL FS Elite 5W-40

0002-000042

Description

FS Elite 5W-40 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection.

FS Elite 5W-40 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear.

Extended oil change intervals as per manufacturer's instructions.

FS Elite 5W-40 offers maximum operational safety in all driving conditions, for example in extreme stop-and-go traffic in big cities, as well as during high-speed motorway driving.

Instructions for use

FS Elite 5W-40 is an energy-efficient engine oil for year-round use, and is ideal for modern petrol and diesel car engines.

Quality classification

Specification

- API SN/CF
- ACEA A3/B4

Approval:

- Lizenziert: API SN
- MB-Freigabe 229.5

ADRIFÖL FS Elite 5W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- BMW Longlife-01
- MB 229.3/226.5
- Porsche A40
- Renault RN0700/0710
- VW 502 00/505 00
- Chrysler MS-10725/12991
- Fiat 9.55535-H2/M2/N2/Z2
- Opel GM-LL-B-025
- PSA B71 2296

Properties

- Excellent cold starting properties, even at low temperatures
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Extensive protection against wear, corrosion and foaming.
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	84,1	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	13,9	MM ² /S	DIN ISO 51562-2
viscosity index	171		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	850	KG/M ³	DIN EN ISO 12185
Pour Point	-42	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.