



Product certificate

ADRIFÖL FS Excellence LS-M 5W-30

0002-000049

Description

ADRIFÖL FS Excellence LS-M 5W-30 is a synthetic smooth-running engine oil with reduced sulfate ash content for petrol and diesel car engines. It is particularly well suited to modern diesel engines with particle filters.

ADRIFÖL FS Excellence LS-M 5W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear.

ADRIFÖL FS Excellence LS-M 5W-30 provides measurable fuel savings and a reduction in emissions due to a reduced HTHS viscosity.

ADRIFÖL FS Excellence LS-M 5W-30 contributes to the protection of the environment. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

ADRIFÖL FS Excellence LS-M 5W-30 is a universal, synthetic smooth-running engine oil, which has been developed especially for modern diesel engines with particle filters.

ADRIFÖL FS Excellence LS-M 5W-30 is suitable for petrol and diesel engines in cars and transporters with and without turbochargers.

Quality classification

Specification

- API SN/CF
- ACEA C2/C3

Approval:

- License: API SN
- MB-Freigabe 229.51
- MB-Freigabe 229.31
- MB-Freigabe 229.52

ADRIFÖL FS Excellence LS-M 5W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- BMW Longlife-04
- Fiat 9.55535-S3
- Renault RN0700/0710
- VW 502 00/505 00/505 01
- Chrysler MS-11106
- dexos2™
- Ford WSS-M2C917-A

Properties

- Excellent cold starting properties, even at low temperatures below -30°
- The function of the hydraulic valve lifter is guaranteed at all temperatures
- Fuel savings under all operating conditions
- A secure lubricant film at high operating temperatures
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming.
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources
- Low SAPS = reduced sulfate ash, phosphorus and sulfur
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	12,100	MM ² /S	DIN ISO 51562-2
viscosity index	166		DIN ISO 2909
appearance	YELLOWBROWN		visually

density at 15°C	848,0	KG/M³	DIN EN ISO 12185
Pour Point	-39,00	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

21.08.2018 02:00:02