



Product certificate

**ADRIFÖL FS Excellence LS Ultra
5W-30**

0002-000045

Description

ADRIFÖL FS Excellence LS Ultra 5W-30 is a synthetic Low SAPS smooth-running engine oil, designed for use in petrol and diesel cars. It is particularly well-suited to use in diesel engines with particle filters.

ADRIFÖL FS Excellence LS Ultra 5W-30 is characterized by its excellent cold starting properties, minimization of fuel consumption, friction and wear.

ADRIFÖL FS Excellence LS Ultra 5W-30 provides measurable fuel savings and a reduction in emissions due to a reduced HTHS viscosity.

ADRIFÖL FS Excellence LS Ultra 5W-30 contributes to the protection of the environment. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

ADRIFÖL FS Excellence LS Ultra 5W-30 is a synthetic smooth-running engine oil, which has been developed especially for diesel engines with particle filters.

ADRIFÖL FS Excellence LS Ultra 5W-30 is suitable for petrol and diesel engines in cars and transporters with and without turbochargers.

Quality classification

Specification

- ACEA C1/C2

ADRIFÖL FS Excellence LS Ultra 5W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Jaguar Land Rover STJLR.03.5005
- Ford WSS-M2C934-A/B

Properties

- Excellent cold starting properties, even at low temperatures below -30°
- The function of the hydraulic valve lifter is guaranteed at all temperatures
- Fuel savings under all operating conditions
- A secure lubricant film at high operating temperatures
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming.
- Low evaporation, thus low oil consumption
- Extended oil change intervals protect natural resources
- Low SAPS = reduced sulphated ash, phosphorous and sulphur

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	50,7	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	9,5	MM ² /S	DIN ISO 51562-2
viscosity index	175		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	844	KG/M ³	DIN EN ISO 12185
Pour Point	-39	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

