



Product certificate

ADRIFÖL FS Low SAPS 0W-30

0002-000510

Description

ADRIFÖL FS Low SAPS 0W-30 is a high-performance engine oil for modern petrol and diesel engines in passenger cars and vans. It is especially recommended for use in engines with turbocharger and multi-valve technology.

Instructions for use

ADRIFÖL FS Low SAPS 0W-30 can be used as a year-round oil. It is suitable for both short-haul operation and long-haul operation.

Quality classification

Specification

- ACEA C2/C3
- API SN/CF

ADRIFÖL FS Low SAPS 0W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- BMW Longlife-04
- MB 229.51/229.31
- VW 502 00/505 00/505 01
- dexos2™
- Renault RN0700/0710

Properties

- Excellent oxidation stability through the use of high quality base oils Safe lubrication
- even at high operating temperatures
- Excellent cold start properties
- High fuel economy (fuel economy)
- Very high wear protection
- Use in petrol and diesel engines from different manufacturers

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	64,33	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	11,77	MM ² /S	DIN ISO 51562-2
Viscosity Index	181		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	845	KG/M ³	DIN EN ISO 12185
Pour Point	-45	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

14.12.2018 13:10:39