



Product certificate

ADRIFÖL FS Low SAPS 5W-40

0002-000512

Description

ADRIFÖL FS Low SAPS 5W-40 is a high-performance engine oil for modern petrol and diesel engines in passenger cars and vans. It is especially recommended for use in engines with turbocharger and multi-valve technology.

Instructions for use

ADRIFÖL FS Low SAPS 5W-40 can be used as a year-round oil. It is suitable for short-haul and long-haul operation. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- ACEA C3
- API SN/CF

ADRIFÖL FS Low SAPS 5W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- BMW Longlife-04
- MB 229.51/229.31/226.5
- Porsche C40
- Renault RN0700/0710
- VW 502 00/505 00/505 01
- Chrysler MS-11106
- dexos2™
- Fiat 9.55535-S2
- Ford WSS-M2C917-A

Properties

- excellent oxidation stability through the use of high quality base oils
- safe lubrication even at high operating temperatures
- excellent cold start properties
- high fuel economy
- very high wear protection
- suitable for use in petrol and diesel engines from different manufacturers

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	80,67	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	13,25	MM ² /S	DIN ISO 51562-2
Viscosity Index	167		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	851	KG/M ³	DIN EN ISO 12185
Pour Point	-39	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

14.01.2019 01:00:08