



Product certificate

ADRIFÖL FS Select 5W-30

0002-000041

Description

ADRIFÖL FS Select 5W-30 is a synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection.

ADRIFÖL FS Select 5W-30 is characterized by its excellent cold starting properties, minimization of friction and wear, as well as a lower fuel consumption. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

ADRIFÖL FS Select 5W-30 is an energy-efficient engine oil for year-round use, and is ideal for all modern petrol and diesel car engines.

ADRIFÖL FS Select 5W-30 can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SL/CF
- ACEA A3/B4

Approval:

- MB-Freigabe 229.5
- VW 502 00 / 505 00
- BMW Longlife-01

ADRIFÖL FS Select 5W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- MB 226.5
- Opel GM-LL-A/B-025
- Renault RN0700/0710

Properties

- Excellent cold starting properties, even at low temperatures below -30°
- A very stable and excellent viscosity behavior and shear stability
- Fuel savings under all operating conditions
- Very good detergent and dispersing properties
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Excellent protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Prevents clogging in the diesel particulate filter
- Extended oil change intervals protect natural resources
-

Technical specifications

| Properties | Data | Unit | Testing under |
|------------------------------|-------------|--------------------|------------------|
| kinematic viscosity at 100°C | 12,1 | MM ² /S | DIN ISO 51562-2 |
| viscosity index | 165 | | DIN ISO 2909 |
| appearance | YELLOWBROWN | | visually |
| density at 15°C | 852 | KG/M ³ | DIN EN ISO 12185 |
| Pour Point | -42 | CELSIUS | ASTM D 7346 |

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

09.07.2018 02:00:29