



Product certificate

ADRIFÖL FS WIV-Combi 5W-30

0002-000035

Description

ADRIFÖL FS WIV-Combi 5W-30 is a synthetic smooth-running engine oil for modern petrol and diesel car engines with or without turbocharging and direct-injection.

ADRIFÖL FS WIV-Combi 5W-30 is characterized by its minimization of fuel consumption, an excellent oil supply during cold starting and ensures a high level of wear and corrosion prevention. Extended oil change intervals as per manufacturer's instructions.

Instructions for use

ADRIFÖL FS WIV-Combi 5W-30 is an energy-efficient engine oil for year-round use and ideal for all modern petrol and diesel car engines.

ADRIFÖL FS WIV-Combi 5W-30 extends the services life of the diesel particulate filter. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- ACEA C3
- API SN

ADRIFÖL FS WIV-Combi 5W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- BMW Longlife-04
- MB 229.51/229.31
- VW 504 00 / 507 00
- Fiat 9.55535-S3
- Porsche C30

Properties

- Excellent cold starting properties
- A very stable and excellent viscosity behavior, even at high speeds, high shear stability
- Fuel savings under all operating conditions
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	70,2	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	12,0	MM ² /S	DIN ISO 51562-2
viscosity index	169		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	849	KG/M ³	DIN EN ISO 12185
Pour Point	-42	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.