



Product certificate

ADRIFÖL Gear Extra 80W-90 GL-5

0002-000202

Description

ADRIFÖL Gear Extra 80W-90 GL-5 is a hypoid gear oil with a mineral oil basis with special high-pressure additives for manual gearboxes. The optimal gear lubrication in all temperature ranges is guaranteed by the high pressure-absorption capacity.

ADRIFÖL Gear Extra 80W-90 GL-5 ensures a stable oil film for lubrication even under extreme conditions. It reduces friction and prevents wear and corrosion.

Instructions for use

ADRIFÖL Gear Extra 80W-90 GL-5 is suitable for use in manual gearboxes for 2-stroke and 4-stroke motorcycles if an oil according to SAE 80W-90 API GL5 is specified.

Quality classification

Specification

- API GL-5

ADRIFÖL Gear Extra 80W-90 GL-5 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- MAN 342 M1, 342 M2
- NATO O-226
- ZF 05A, 07A, 08, 12E, 16B-D, 17B, 19B, 21A
- SAE J2360
- SCANIA STO 1:0
- VOLVO 1273.10

Properties

- Very good oxidation stability
- Good resistance to ageing
- Excellent viscosity-temperature characteristics
- Wear protection
- Protection against rust & corrosion, attack on non-ferrous metals
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	14,12	MM ² /S	DIN ISO 51562-2
viscosity index	100		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	889,8	KG/M ³	DIN EN ISO 12185
Pour Point	-33	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:55:58