



Product certificate

ADRIFÖL Gear Extra 85W-140

0002-000203

Description

ADRIFÖL Gear Extra 85W-140 is a lubricant for mechanical gearboxes on a basis of solvent refined base oils and special additives which give the lubricant excellent properties.

Instructions for use

ADRIFÖL Gear Extra 85W-140 is used in maximum duty, hypoid-geared gears such as axle drives and manual gearboxes.

Quality classification

Specification

- API GL-5

ADRIFÖL Gear Extra 85W-140 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- MIL-L-2105D

Properties

- Very good oxidation stability
- No foam formation
- Low pour point
- Protection against rust & corrosion
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	26,4	MM ² /S	DIN ISO 51562-2
viscosity index	99		DIN ISO 2909
appearance	gelbbraun		visually
density at 15°C	903	KG/M ³	DIN EN ISO 12185
Pour Point	-27	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

27.07.2018 02:00:21