



## Product certificate

**ADRIFÖL Gear Extra Full Synth. LS  
75W-140 GL 5**

**0002-000222**

### Description

ADRIFÖL Gear Extra Full Synth. LS 75W-140 GL-5 is a synthetic multi-purpose oil for highly stressed manual gearboxes. ADRIFÖL Gear Extra Full Synth LS 75W-140 GL 5 was developed based on the high quality fully synthetic base oils (PAO and Ester) with a special additive treatment and inhibition for limited slip applications.

ADRIFÖL Gear Extra Full Synth. LS 75W-140 GL-5 is coordinated to the increased loads of manual gearbox oils, in order to ensure the gearbox functions flawlessly.

### Instructions for use

ADRIFÖL Gear Extra Full Synth. LS 75W-140 GL-5 guarantees proper lubrication, even in self-locking, hypoid-geared gearboxes. The operating instructions of the automobile and gearbox manufacturer must be observed.

### Quality classification

#### Specification

- API GL-5

**ADRIFÖL Gear Extra Full Synth. LS 75W-140 GL 5 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

### Properties

- Excellent viscosity-temperature characteristics
- Less wear
- Very good oxidation stability
- Resistant oil film
- Neutral towards metal and sealing agents.
- 

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	24,800	MM <sup>2</sup> /S	DIN ISO 51562-2
viscosity index	186		DIN ISO 2909
appearance	LIGHT YELLOW		visually
density at 15°C	871,2	KG/M <sup>3</sup>	DIN EN ISO 12185
Pour Point	-48	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

11.01.2019 01:00:15