



Product certificate

ADRIFÖL Gear Super LS 85W-90

0002-000220

Description

ADRIFÖL Gear Super LS 85W-90 GL-5 is a multipurpose gear oil for high performance manual gearboxes.
ADRIFÖL Gear Super LS 85W-90 GL-5 was developed based on the highest quality synthetic base oils with a special additive treatment and inhibition for limited slip applications.
ADRIFÖL Gear Super LS 85W-90 GL-5 was designed with the increased loads of manual gearbox oils in mind to ensure the gearbox functions flawlessly.

Instructions for use

ADRIFÖL Gear Super LS 85W-90 GL-5 is especially suitable for lubricating differentials with limited slip.
ADRIFÖL Gear Super LS 85W-90 GL-5 guarantees proper lubrication, even in self-locking, hypoid-geared gearboxes. The operating instructions of the automobile and gearbox manufacturer must be observed.

Quality classification

Specification

- API GL-5

ADRIFÖL Gear Super LS 85W-90 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- MIL-L-2105 D
- ZF TE-ML 16C, 05C, 12C, 16E
- Ford Spezifikation

Properties

- Excellent viscosity-temperature characteristics
- Less wear
- Very good oxidation stability
- Resistant oil film
- Neutral towards metal and sealing agents.
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	14,900	MM ² /S	DIN ISO 51562-2
viscosity index	108		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	890,3	KG/M ³	DIN EN ISO 12185
Pour Point	-33	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:56:28