



## Product certificate

**ADRIFÖL Gear Super LS SAE 90 GL-5**

**0002-000198**

### Description

ADRIFÖL Gear Super LS SAE 90 GL-5 is an oil for manual gearboxes designed on the basis of mineral oils and special additives. At high temperatures, an optimal gear lubrication is ensured.

Due to the special additives, ADRIFÖL Gear Super LS SAE 90 GL-5 is suitable for use in limited slip differentials (limited slip properties).

ADRIFÖL Gear Super LS SAE 90 GL-5 reduces friction and prevents wear and corrosion. Even under extreme dynamic conditions, a stable oil film is guaranteed for the lubrication.

### Instructions for use

ADRIFÖL Gear Super LS SAE 90 GL-5 guarantees proper lubrication, even in self-locking, hypoid-geared gearboxes. The operating instructions of the automobile and gearbox manufacturer must be observed.

### Quality classification

#### Specification

- API GL-5

**ADRIFÖL Gear Super LS SAE 90 GL-5 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

- MAN 342 M2 (160,000 km)
- MIL-L-2105D
- ZF TE-ML 05A, 7A, 12E, 16B-D, 17B 19B, 21A

### Properties

- Less wear
- Very good oxidation stability
- Resistant oil film
- Neutral towards metal and sealing agents.
- 

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	16,000	MM <sup>2</sup> /S	DIN ISO 51562-2
viscosity index	97		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	897,0	KG/M <sup>3</sup>	DIN EN ISO 12185
Pour Point	-18	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

27.07.2018 02:00:19