



Product certificate

**ADRIFÖL Gear Super Synth. LS
75W-90 GL 5**

0002-000213

Description

ADRIFÖL Gear Extra Full Synth. LS 75W-90 GL-5 is a synthetic multi-purpose oil for highly stressed manual gearboxes.

ADRIFÖL Gear Extra Full Synth. LS 75W-90 GL-5 was developed based on the synthetic base oils with a special additive treatment and inhibition for limited slip applications.

ADRIFÖL Gear Extra Full Synth. LS 75W-90 GL-5 is coordinated to the increased loads of manual gearbox oils, in order to ensure the gearbox functions flawlessly.

Instructions for use

ADRIFÖL Gear Extra Full Synth. LS 75W-90 GL-5 is especially suitable for lubricating differentials with limited slip.

ADRIFÖL Gear Extra Full Synth. LS 75W-90 GL-5 guarantees proper lubrication, even in self-locking, hypoid-geared gearboxes. The operating instructions of the automobile and gearbox manufacturer must be observed.

Quality classification

Specification

- API GL-5

ADRIFÖL Gear Super Synth. LS 75W-90 GL 5 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- MIL-L-2105D
- ZF TE-ML 05C/D

Properties

- Excellent viscosity-temperature characteristics
- Less wear
- Excellent high-pressure properties
- Protection against foaming
- Excellent "Limited Slip" properties
- Neutral towards metal and sealing agents.

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	14,500	MM ² /S	DIN ISO 51562-2
viscosity index	187		DIN ISO 2909
appearance	LIGHT YELLOW		visually
density at 15°C	869,0	KG/M ³	DIN EN ISO 12185
Pour Point	-45	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

28.09.2018 02:00:12