



## Product certificate

**ADRIFÖL Gear Super Synth. LX  
75W-85 GL-5**

**0002-000216**

### Description

ADRIFÖL Gear Super Synth. LX 75W-85 GL-5 is a synthetic rear axle transmission fluid for highly stressed transmissions. It was developed based on synthetic base oils with a special additive and inhibition for limited slip applications.

ADRIFÖL Gear Super Synth. LX 75W-85 GL-5 is adapted to the increased stress on transmission fluids, to ensure the proper functioning of the transmission.

### Instructions for use

ADRIFÖL Gear Super Synth. LX 75W-85 GL-5 is specifically for the lubrication of transfer cases and differential gears with limited slip. ADRIFÖL Gear Super Synth. LX 75W-85 GL-5 was specifically developed for Toyota and Lexus.

ADRIFÖL Gear Super Synth. LX 75W-85 GL-5 ensures the proper lubrication of transmissions. Please observe the operating instructions from the car and transmission manufacturers.

### Quality classification

#### Specification

- API GL-5
- MT-1, MIL-L2105E
- SAE J2360

**ADRIFÖL Gear Super Synth. LX 75W-85 GL-5 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

- BMW
- Dodge
- Jeep
- Lexus
- Mercedes-Benz
- Toyota

### Properties

- Excellent viscosity-temperature behavior
- Minimal wear
- Excellent extreme pressure properties
- Prevention of foam generation
- Excellent limited slip properties
- Neutral behaviour towards metal and sealing materials
- 

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	11,100	MM <sup>2</sup> /S	DIN ISO 51562-2
viscosity index	173		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	865,0	KG/M <sup>3</sup>	DIN EN ISO 12185
Pour Point	-48	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.