



Product certificate

ADRIFÖL HC 0W-30

0002-000037

Description

HC 0W-30 is a synthetic smooth-running engine oil for petrol and diesel car engines of light transporters and high-performance vehicles with or without turbocharger and direct injection. HC 0W-30 guarantees a high operational reliability in all driving conditions such as extreme stop-and-go traffic as well as high-speed motorway driving.

Instructions for use

HC 0W-30 is an energy efficient engine oil for year-round use, and can be used in modern petrol and diesel car engines.

HC 0W-30 is suitable for extended oil change intervals and extends the lifespan of the particulate filter. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API SL/CF
- ACEA A3/B4

ADRIFÖL HC 0W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- BMW Longlife-01
- MB 229.5/229.3
- VW 502 00/505 00
- Opel GM-LL-A/B-025
- Renault RN0700/0710
- Volvo VCC 95200356

Properties

- A very stable and excellent viscosity behavior and shear stability
- Fuel savings due to smooth-running characteristics
- Long lifespan due to high oxidation stability
- Prevents black sludge from forming
- Low evaporation, thus low oil consumption
- Excellent protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	68,1	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	12,2	MM ² /S	DIN ISO 51562-2
viscosity index	178		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	848	KG/M ³	DIN EN ISO 12185
Pour Point	-42	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.