



Product certificate

ADRIFÖL HSS SHPD 15W-40

0002-000109

Description

ADRIFÖL HSS SHPD 15W-40 is a high-quality SHPD multigrade engine oil for diesel car and lorry engines of all makes, with or without turbocharging. ADRIFÖL HSS SHPD 15W-40 is suitable for year-round use in all engines. minimization of friction, wear and fuel consumption, excellent cold starting properties. ADRIFÖL HSS SHPD 15W-40 facilitates extended oil change intervals as per manufacturer's instructions.

Instructions for use

ADRIFÖL HSS SHPD 15W-40 can be used in a mixed fleet in engines with the specifications indicated.

It is suitable for modern diesel vehicles that meet the Euro V emission standard. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- API CI-4 / SL, ACEA E7

ADRIFÖL HSS SHPD 15W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- A very stable and excellent viscosity behavior
- High oxidation stability, high pressure absorption capacity
- an excellent resistance to ageing
- High safety margin even in boundary lubrication
- Ideal for difficult operating conditions
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	15,8	MM ² /S	DIN ISO 51562-2
viscosity index	148		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	877	KG/M ³	DIN EN ISO 12185
Pour Point	-39	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

03.10.2018 02:00:05