



## Product certificate

**AVENO Hydraulic HVLP 15**

**0002-000241**

### Description

AVENO Mineral Hydraulic HVLP 15 is a multigrade hydraulic oil developed on the basis of specially selected base oils.

AVENO Mineral Hydraulic HLVP 15 is characterized especially by a very good viscosity and temperature behavior and reliable corrosion protection.

### Instructions for use

AVENO Mineral Hydraulic HVLP 15 is suitable for all industrial and mobile hydraulic systems of heavy-loaded constructions. Favoured at strongly fluctuating operating temperatures. May not be used in hydraulic systems which contain silver or silver-plated construction and operating elements

### Quality classification

#### Specification

#### Approval:

- Pour Point
- kinematic viscosity at 40°C
- viscosity index

**AVENO Hydraulic HVLP 15 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

- CETOP RP 91H-HV
- DENISON HF-1, HF-0, HF-2
- General Motors LH-04-1
- General Motors LH-06-1
- General Motors LH-15-1
- ISO 6743/4-HV
- AFNOR 48 603 HV
- Sperry Vickers 1-286-S
- Sperry Vickers M-2950-S
- US Steel 127
- US Steel 136

### Properties

- A very good air and water separation capacity to prevent foam formation
- An excellent protection against wear and corrosion
- A high and stable viscosity index
- A low pour point
- Neutrality towards sealants made from plastics
- A very stable and excellent viscosity and temperature behaviour
- 

### Technical specifications

Properties	Data	Unit	Testing under
------------	------	------	---------------

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:57:08