



Product certificate

ADRIFÖL Hydraulic HVLP 32 Super Clear

0002-000256

Description

ADRIFÖL Hydraulic HVLP 32 Super Clear is a multi-grade hydraulic oil. ADRIFÖL Hydraulic HLVP 32 Super Clear offers a high wear protection, even under extreme loads, thanks to effective additives.

ADRIFÖL Hydraulic HLVP 32 Super Clear is characterized especially by a very good viscosity and temperature behavior and reliable corrosion protection.

Instructions for use

ADRIFÖL Hydraulic HVLP 32 Super Clear can be used primarily in hydraulic systems with heavily fluctuating operating temperatures.

ADRIFÖL Hydraulic HVLP 32 Super Clear is ideal for heavy-loaded hydraulic systems, earth-moving machines and agricultural machinery. It is favoured at heavily fluctuating operating temperatures and may not be used in hydraulic systems which contain silver or silver-plated construction and operating elements.

Quality classification

Specification

- DIN 51524 Teil3 HVLP

ADRIFÖL Hydraulic HVLP 32 Super Clear is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- CETOP RP 91H-HV
- General Motors LH-04-1
- General Motors LH-06-1
- General Motors LH-15-1
- ISO 6743/4-HV
- Sperry Vickers 1-286-S
- AFNOR 48 603 HV
- DENISON HF-1, HF-0, HF-2
- Sperry Vickers M-2950-S
- US Steel 127
- US Steel 136

Properties

- reliable protection against corrosion
- excellent wear protection
- a stable viscosity index
- very good oxidation stability
- prevention of foam formation thanks to good air and water separation capacity
- very low pour point
- neutral towards sealing agents
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	29,800	MM ² /S	DIN ISO 51562-2
viscosity index	162		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	854,0	KG/M ³	DIN EN ISO 12185
Pour Point	-45	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:57:40