



Product certificate

ADRIFÖL LE Diesel Performance 15W-40

0002-000105

Description

ADRIFÖL LE-Diesel Performance 15W-40 is a high-quality lorry engine oil which is formulated with Low SAPS technology. It can be used in both older and newer engines.

ADRIFÖL LE-Diesel Performance 15W-40 improves the performance, reliability and cleanliness of engines. It reduces the fuel consumption and wear, as it reduces friction.

Instructions for use

ADRIFÖL LE-Diesel Performance 15W-40 is ideal for use in Euro 6 engines with exhaust systems and in Euro 3, 4, 5 engines, if this is prescribed by the engine manufacturer.

Quality classification

Specification

- ACEA E9-08
- API CJ-4 / CI-4+ / CI-4, SM/CF

Approval:

- Cummins CES 20081
- MB-Freigabe 228.31
- Volvo VDS-4
- Mack EO-O Premium Plus
- Renault VI RLD-3

ADRIFÖL LE Diesel Performance 15W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Caterpillar ECF-2, ECF-3
- Deutz DQC III-10 LA
- John Deere JDQ 78 X
- MAN M3575
- MTU Type 2.1
- DDC 93K218
- Global DHD-1
- JASO DH-2

Properties

- Stable viscosity behaviour
- Protection against silting, coking & varnish
- Excellent detergent & dispersing properties
- Very good wear and corrosion protection
- High oxidation stability & engine cleanliness

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	100,800	MM²/S	DIN ISO 51562-2
kinematic viscosity at 100°C	14,47	MM²/S	DIN ISO 51562-2
viscosity index	146		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	875,5	KG/M³	DIN EN ISO 12185
Pour Point	-36	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.