



## Product certificate

**ADRIFÖL LL Professional 0W-30**

**0002-000069**

### Description

ADRIFÖL LL Professional 0W-30 is a fully synthetic smooth-running engine oil for petrol and diesel car engines with or without turbocharging and direct injection. Minimization of friction, wear and fuel consumption, excellent cold starting properties. Extended oil change intervals as per manufacturer's instructions.

ADRIFÖL LL Professional 0W-30 extends the operational life of the diesel particulate filter by reducing the concentration of ash-forming particles in the exhaust gas. Reduces the release of harmful emissions into the environment. Offers increased safety due to continuously high protection of the engines. It achieves a high viscosity index thanks to its formulation with special base oils.

### Instructions for use

ADRIFÖL LL Professional 0W-30 is an energy-efficient engine oil for year-round use, and is ideal for use in modern petrol and diesel engines.

ADRIFÖL LL Professional 0W-30 ensures extended oil change intervals and extends the lifespan of the particulate filter. The operating instructions of the automobile and engine manufacturers must be observed.

### Quality classification

#### Specification

- API SN
- ACEA C3

#### Approval:

- VW 504 00/507 00

**ADRIFÖL LL Professional 0W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:**

- BMW Longlife-04
- Fiat 9.55535-S3
- MB 229.51/229.31
- Porsche C30

### Properties

- Excellent cold starting properties, even at low temperatures below -25°
- A very stable and excellent viscosity behavior and shear stability
- Fuel savings under all operating conditions
- Secure lubricant film at high operating temperatures
- Neutrality towards sealants
- Low evaporation, thus low oil consumption
- Excellent protection against wear, corrosion and foaming.
- Suitable for catalytic converters
- Extended oil change intervals protect natural resources

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	60,6	MM <sup>2</sup> /S	DIN ISO 51562-2
kinematic viscosity at 100°C	11,8	MM <sup>2</sup> /S	DIN ISO 51562-2
viscosity index	194		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	845	KG/M <sup>3</sup>	DIN EN ISO 12185
pour point	-48	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

