



Product certificate

ADRIFÖL Mineral Hydraulic HLP 220

0002-000233

Description

ADRIFÖL Mineral Hydraulic HLP 220 is an optimally alloyed hydraulic oil. It has a high level of performance and a wide range of applications within the entire industry. ADRIFÖL Mineral Hydraulic HLP 220 offers an excellent wear protection under extreme loads.

ADRIFÖL Mineral Hydraulic HLP 220 is characterized especially by a very good viscosity and temperature behavior, high resistance to ageing and reliable corrosion protection.

Instructions for use

ADRIFÖL Mineral Hydraulic HLP 220 is used as a hydraulic fluid in practically all hydraulic systems. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- DIN 51506, Teil 2
- DIN 51506 VC

ADRIFÖL Mineral Hydraulic HLP 220 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- ISO 6743/4-HV
- AFNOR NF E 48-603 (HM, HV)

Properties

- High level of performance
- Very good viscosity and temperature behavior
- High resistance to ageing
- Excellent wear protection
- Reliable corrosion protection, neutral towards sealants
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	237	MM ² /S	DIN ISO 51562-2
viscosity index	92		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	897	KG/M ³	DIN EN ISO 12185
Pour Point	-12	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:56:53