



Product certificate

ADRIFÖL Mineral SAE 80 GL 4

0002-000199

Description

ADRIFÖL Mineral SAE 80 GL-4 is an oil for manual gearboxes designed on the basis of mineral oils and special additives. At high temperatures, an optimal gear lubrication is ensured.

ADRIFÖL Mineral SAE 80 GL-4 reduces friction and prevents wear and corrosion. Even under extreme dynamic conditions, a stable oil film is guaranteed for the lubrication.

Instruktionen for use

ADRIFÖL Mineral SAE 80 GL-4 guarantees proper lubrication, even in hypoid-geared gearboxes. The operating instructions of the automobile and gearbox manufacturer must be observed.

Quality classification

Specification

- API GL-4

ADRIFÖL Mineral SAE 80 GL 4 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- Less wear
- Very good oxidation stability
- Resistant oil film
- Neutral towards metal and sealing agents.
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C	10,100	MM ² /S	DIN ISO 51562-2
viscosity index	102		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	878,0	KG/M ³	DIN EN ISO 12185
Pour Point	-30	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

16.03.2018 12:37:16