



Product certificate

ADRIFÖL Mineral SAE 80 GL 5

0002-000200

Description

Less wear

Very good oxidation stability

Resistant oil film

Neutral towards metal and sealing agents.

ADRIFÖL Mineral SAE 80 GL-5 is an oil for manual gearboxes designed on the basis of mineral oils and special additives. At high temperatures, an optimal gear lubrication is ensured.

ADRIFÖL Mineral SAE 80 GL-5 reduces friction and prevents wear and corrosion. Even under extreme dynamic conditions, a stable oil film is guaranteed for the lubrication.

Instructions for use

ADRIFÖL Mineral SAE 80 GL-5 guarantees proper lubrication, even in hypoid-geared gearboxes. The operating instructions of the automobile and gearbox manufacturer must be observed.

Quality classification

Specification

- API GL-5

ADRIFÖL Mineral SAE 80 GL 5 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 100°C		MM ² /S	DIN ISO 51562-2
viscosity index			DIN ISO 2909
appearance			visually
density at 15°C		KG/M ³	DIN EN ISO 12185
Pour Point		CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:55:54