# Product certificate

## ADRIFÖL MotorCycle 4 Stroke 10W-60 — 0002-000136

## Description

ADRIFÖL MotorCycle 4 Stroke 10W-60 is a heavy-duty engine oil for demanding 4-stroke motorbikes. It allows for fuel-saving engine operation and is specifically designed for wet and lubricated couplings.
ADRIFÖL MotorCycle 4 Stroke 10W-60 is characterized by its excellent cold starting properties, as it ensures optimum lubrication reliability during the cold-running phase.

## Instructions for use

ADRIFÖL MotorCycle 4 Stroke 10W-60 is especially suitable as a high-performance, smooth-running engine oil for all motorcycles, when the specification SAE 10W-60 is required.
ADRIFÖL MotorCycle 4 Stroke 10W-60 meets the high-tech demands of the latest high-performance engine generation.

## Quality classification

### Specification

- API SL

### ADRIFÖL MotorCycle 4 Stroke 10W-60 is tried and tested in practice in aggregates requiring adherence to manufacturer’s fluid specifications:

- JASO MA
- JASO MA 2

## Properties

- Excellent cold starting properties
- Very stable viscosity index
- Very good detergent and dispersing properties
- Fast lubrication of the engine
- Low evaporation, thus low oil consumption
- Prevention of silting, varnish, coking and corrosion
- Prevention of oil-dependent deposits in combustion cham-bers, in the piston ring area or on valves
-

## Technical specifications

| Properties | Data | Unit | Testing under |
|---|---|---|---|
| kinematic viscosity at 40°C | 174,000 | MM²/S | DIN ISO 51562-2 |
| kinematic viscosity at 100°C | 23,900 | MM²/S | DIN ISO 51562-2 |
| viscosity index | 169 | | DIN ISO 2909 |
| appearance | YELLOWBROWN | | visually |
| density at 15°C | 858,0 | KG/M³ | DIN EN ISO 12185 |
| Pour Point | -39 | CELSIUS | ASTM D 7346 |

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:54:44