Product certificate

ADRIFÖL MotorCycle 4 Stroke Mineral 20W-50 — 0002-000126

Description

ADRIFÖL MotorCycle 4 Stroke Mineral 20W-50 is a mineral-based engine oil with selected additives for demanding 4-stroke motorbikes. It is characterized by its high durability and reliability and is specifically designed for wet and lubricated couplings.
ADRIFÖL MotorCycle 4 Stroke Mineral 20W-50 has an outstanding lubrication film adhesion and good shear stability as well as excellent cleaning properties and high resistance to ageing.

Instructions for use

ADRIFÖL MotorCycle 4 Stroke Mineral 20W-50 is a suitable engine oil for all motorcycles, when the specification SAE 20W-50 JASO MA/MA2 is required.

Quality classification

Specification

- API SM
- JASO MA2

ADRIFÖL MotorCycle 4 Stroke Mineral 20W-50 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- Excellent cold starting properties
- High oxidation stability
- Excellent shear stability
- Very good detergent and dispersing properties
- Very good viscosity-temperature behaviour
- Suitable for catalytic converters
- High safety margin even in boundary lubrication
- Prevents black sludge from forming
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	166,000	MM²/S	DIN ISO 51562-2
kinematic viscosity at 100°C	19,000	MM²/S	DIN ISO 51562-2
viscosity index	130		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	882,0	KG/M³	DIN EN ISO 12185
Pour Point	-30	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:54:31