



Product certificate

ADRIFÖL Premium UHPD 5W-30

0002-000571

Description

ADRIFÖL Premium UHPD 5W-30 is a smooth-running engine oil for all diesel engines with and without turbo charging in lorries, buses and machinery. It has an excellent flow behavior, even at low temperatures. It quickly reaches critical lubrication points, thus ensuring a considerable reduction in wear during the warm-up phase. Selected active ingredients ensure maximum engine cleanliness, even in short-haul traffic. ADRIFÖL Premium UHPD 5W-30 allows for extended oil change intervals in accordance with manufacturer's instructions, and high wear protection with low oil and fuel consumption.

Instructions for use

ADRIFÖL Premium UHPD 5W-30 is ideal for mixed fleets. IT can be used in engines with the specifications indicated. The operating instructions of the automobile and engine manufacturer must be observed.

Quality classification

Specification

- ACEA E4/E7
- JASO DH-1
- API CI-4
- Global DHD-1

ADRIFÖL Premium UHPD 5W-30 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Caterpillar ECF-2
- MAN 3377/3277
- MB 228.5
- MTU Type 3
- VOLVO VDS-3
- Cummins CES 20076/78
- Deutz DQC IV-10
- MACK EO-N/EO-M Plus
- Renault RXD/RLD-2
- Scania LDF

Properties

- Reduction in fuel consumption due to smooth running characteristics
- Fastest possible lubrication after starting
- Protection against formation of mirror surfaces on cylinder tracks
- Reduction of exhaust gas particles
- Protection against corrosion, silting and bonding
- Environmental friendliness due to longest oil change intervals

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	71,100	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	12,000	MM ² /S	DIN ISO 51562-2
viscosity index	168		DIN ISO 2909
appearance	YELLOW		visually
density at 15°C	854,0	KG/M ³	DIN EN ISO 12185
Pour Point	-45	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.