



Product certificate

ADRIFÖL Racing 15W-50

0002-000145

Description

ADRIFÖL Racing 15W-50 is a modern, semi-synthetic, multigrade engine oil designed on a basis of especially high-quality base oils. It is ideal for a sporty driving style thanks to its very high viscosity index and good shear stability. ADRIFÖL Racing 15W-50 is ideally suited to modern petrol engines under the heaviest of loads during car racing. ADRIFÖL Racing 15W-50 maintains a secure lubrication layer, even at very high operating temperatures.

Instructions for use

ADRIFÖL Racing 15W-50 can be used as a special oil for car racing, even under the harshest of conditions.

Quality classification

Specification

- ACEA A3/B4
- API SN/CF

ADRIFÖL Racing 15W-50 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- MB 229.1

Properties

- Excellent cold starting properties
- Low friction loss
- Prevention of sludge formation
- A very stable and excellent viscosity behavior and shear stability
- Low evaporation, thus low oil consumption
- Extensive protection against wear, corrosion and foaming
- Extended oil change intervals protect natural resources

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	139,100	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	18,730	MM ² /S	DIN ISO 51562-2
viscosity index	152		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	869,0	KG/M ³	DIN EN ISO 12185
Pour Point	-36	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

23.07.2018 02:00:30