



Product certificate

ADRIFÖL Racing Ultimate 10W-60

0002-000147

Description

ADRIFÖL Racing Ultimate 10W-60 is a fully synthetic, multi-grade engine oil with specially selected base oils. A very high proportion of Group V poly-alpha-olefins makes it a very special engine oil, which can also satisfy the highest requirements. Thanks to its special additives, ADRIFÖL Racing Ultimate 10W-60 is also suitable for extreme racing.

ADRIFÖL Racing Ultimate 10W-60 is ideally suited to modern petrol engines under the heaviest of loads during car racing. ADRIFÖL Racing Ultimate 10W-60 ensures an optimal lubrication layer, even at very high operating temperatures.

Instructions for use

ADRIFÖL Racing Ultimate 10W-60 was specially developed for speedway car racing and may therefore also be used in the harshest operating conditions. Its particularly modern and high-quality basic ingredients, in combination with a very specially selected additive package, prevent deposits on engine parts that are subject to high stress.

Quality classification

Specification

- ACEA A3/B4
- API SN/CF

ADRIFÖL Racing Ultimate 10W-60 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- A highly-modern, fully-synthetic engine oil for use in extreme racing
- A very stable and excellent viscosity behaviour and shear stability
- High oil film stability to prevent wear
- Continuous high oil pressure
- Low evaporation, thus low oil consumption
- Highest possible protection against wear, corrosion and foaming
- Suitable for catalytic converters
- Black sludge is prevented from forming
- Extended oil change intervals protect natural resources
-

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	170,000	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	25,100	MM ² /S	DIN ISO 51562-2
viscosity index	181		DIN ISO 2909
appearance	YELLOW		visually
viscosity CCS	5830	MPAS	ASTM D 5293
density at 15°C	860,0	KG/M ³	DIN EN ISO 12185
Pour Point	-45	CELSIUS	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

