



## Product certificate

**ADRIFÖL STOU 10W-40**

**0002-000122**

### Description

ADRIFÖL STOU 10W-40 is a modern multi-purpose oil for agricultural machines, excavators and construction equipment.

ADRIFÖL STOU 10W-40 is manufactured from high-quality base oils and selected additives and can be used equally in engines, gearboxes and hydraulic systems of modern agricultural machinery.

### Instructions for use

ADRIFÖL STOU 10W-40 is suitable for year-round use as an engine oil for petrol engines and aspirated and turbocharged diesel engines, as a gear oil (including wet brakes) and as a hydraulic oil in tractors and agricultural machinery.

ADRIFÖL STOU 10W-40 can also be used as a compressor oil.

### Quality classification

#### Specification

- API CG-4/ SF
- API GL-4
- ACEA E3
- HVLP D (DIN 51524 Teil 3)

#### ADRIFÖL STOU 10W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Allison C4
- Fendt KDM 41.2011
- Ford ESN-M2C 134 B/C/D, 159B/C
- John Deere J20C/D, J27
- Massey Ferguson CMS 1145, 1144, 1139
- MB 227.1, MB 228.1, MB 228.3
- ZF TE ML 06A, 06B, 06C, 06D, 06F, 07B
- Caterpillar TO-2
- MAN 271
- MAT 3525
- MIL-L-2104D
- New Holland NH 410B

### Properties

- Outstanding high-pressure properties
- A high dispersion and detergent capability
- Protection against wear, corrosion and foaming
- High oxidation stability
- A high and stable viscosity index
- 

### Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	84,69	MM <sup>2</sup> /S	DIN ISO 51562-2
kinematic viscosity at 100°C	12,9	MM <sup>2</sup> /S	DIN ISO 51562-2
viscosity index	152		DIN ISO 2909
appearance	YELLOWBROWN		visually
density at 15°C	869,0	KG/M <sup>3</sup>	DIN EN ISO 12185
Pour Point	-39	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

