



Product certificate

ADRIFÖL STOU 15W-40

0002-000117

Description

ADRIFÖL STOU 15W-40 is a modern multi-purpose oil for agricultural machines, excavators and construction equipment.

ADRIFÖL STOU 15W-40 is manufactured from high-quality base oils and selected additives and can be used equally in engines, gearboxes and hydraulic systems of modern agricultural machinery.

Instructions for use

ADRIFÖL STOU 15W-40 is suitable for year-round use as an engine oil for petrol engines and aspirated and turbocharged diesel engines, as a gear oil (including wet brakes) and as a hydraulic oil in tractors and agricultural machinery.

Quality classification

Specification

- ACEA E2
- API GL-4
- API SF/CF/CG-4

ADRIFÖL STOU 15W-40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Allison C-4
- Caterpillar TO-2
- Ford M2C159B
- MB 227.1/MB 228.1/MB 228.3
- ZF TE-ML 06A/06B/06C/06D/07B
- John Deere J 27
- MAN 271
- Massey Ferguson CMS 1139/1144/1145
- MIL-L-2104D

Properties

- Outstanding high-pressure properties
- A high dispersion and detergent capability
- Protection against wear, corrosion and foaming
- High oxidation stability
- A high and stable viscosity index

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	83.6	MM ² /S	DIN ISO 51562-2
kinematic viscosity at 100°C	13.1	MM ² /S	DIN ISO 51562-2
viscosity index	157		DIN ISO 2909
appearance	brown		visually
density at 15°C	868	KG/M ³	DIN EN ISO 12185
Pour Point	-39	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

15.10.2018 14:12:58