



Product certificate

0002-000305

Description

ADRIFÖLSuperFeinmechanikölisresin and acid-free.

ADRIFÖLSuperFeinmechanikölisdeparaffined and treated in a hydrofinishing process.

Instructions for use

ADRIFÖL Super Feinmechaniköl can be used as a universal oil for bikes, sewing machines, household and office equipment, locks, tools etc.

Quality classification

Specification

is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

Properties

- Bright colour
- Mild odour
- Low sulphur content
- Good viscosity-temperature behaviour
- Ageing-resistant oil
-

Technical specifications

| Properties | Data | Unit | Testing under |
|------------------------------|--------|--------------------|------------------|
| kinematic viscosity at 40°C | 21,470 | MM ² /S | DIN ISO 51562-2 |
| kinematic viscosity at 100°C | 4,331 | MM ² /S | DIN ISO 51562-2 |
| viscosity index | 109 | | DIN ISO 2909 |
| appearance | YELLOW | | visually |
| density at 15°C | 857,0 | KG/M ³ | DIN EN ISO 12185 |
| Pour Point | -15 | CELSIUS | ASTM D 7346 |

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

04.07.2018 11:59:18