Product certificate

ADRIFÖL Super Truck 40 0002-000086

Description

Super Truck 40 is an HD engine oil, high-alloyed with synthetic additives suitable for diesel lorry engines, including with turbo charging.
With Super Truck 40, a reliable and heavy-duty engine oil has been developed, which also offers safety reserves.

Instructions for use

Super Truck 40 is an engine oil for year-round use, and is suitable for diesel engines and commercial vehicle engines with and without turbo charging.
Super Truck 40 can be used in engines with the specifications indicated. The operating instructions of the engine manufacturer must be observed.

Quality classification

Specification

- API CF-4/SG
- ACEA E2/B4

ADRIFÖL Super Truck 40 is tried and tested in practice in aggregates requiring adherence to manufacturer's fluid specifications:

- Allison C-4
- Caterpillar TO-2
- Deutz DQC I-02
- MAN 270
- MB 228.0/235.12
- MIL-L-2104 D
- MTU Type 1
- ZF TE-ML 02H/04A/04B

Properties

- A stable and excellent viscosity behaviour
- Good detergent and dispersing properties
- Neutrality towards sealants
- Extensive protection against wear, corrosion and foaming
- Suitable for catalytic converters
- A very good shear stability
- Prevention of black sludge formation
- High safety margin even in boundary lubrication
- A high oxidation stability

Technical specifications

Properties	Data	Unit	Testing under
kinematic viscosity at 40°C	131,5	MM²/S	DIN ISO 51562-2
kinematic viscosity at 100°C	14,3	MM²/S	DIN ISO 51562-2
viscosity index	108		DIN ISO 2909
appearance	brown		visually
density at 15°C	885,9	KG/M³	DIN EN ISO 12185
Pour Point	-18	°C	ASTM D 7346

All declared values are approximate and subject to standard production variations.

To the best of our knowledge all information reflects the current state of findings and our development. Subject to change. Any reference to DIN standards are solely for product description purposes and do not represent a guarantee. If problems arise, please consult a technician.

05.12.2018 01:00:13